

DOUTHITT HEAVY DUTY Flexographic Platemaker MODEL DCOPXF



- **GATF Award-winning Option “X” Vacuum System Guarantees Fastest Contact and Best Registration**
- **High Wattage Point Light With Heavy Duty Diffusion Filter**

Plate Size	Crating	Approx. Floor Space	Crated Weight
30 x 35	No chg.	40 x 47	1350 lbs.
35 x 40	No chg.	47 x 55	1450 lbs.
40 x 45	No chg.	53 x 60	1550 lbs.
48 x 55	No chg.	61 x 70	1750 lbs.

PRICE INCLUDES:

- (1) Douthitt’s OPTION “X” Vacuum system, an electronically controlled inverse air evacuation system that starts the vacuum in the center of the frame and moves it outward to the edges eliminating the trapping of air. OPTION “X” gives you the fastest, most consistent overall contact and the best registration.
- (2) Complete Olite AL 53 Tri-Level 5000 Watt Printing Lamp Assembly. For more details on the Printing Lamps see page 16.
- (3) Heavy Duty Motorized Diffusion Filter for controlling exact dot/shoulder specification.
- (4) Automated controls simplify the operation for multiple exposure needs. Standard with 31 channels of memory and battery back up.
- (5) Printing Lamp can be raised and lowered by means of counterbalanced weight concealed inside unit, guaranteeing optimum coverage.
- (6) Spring Loaded Back is furnished on the blanket frame allowing any height register pins or contact boards of any thickness.

OPTIONAL ACCESSORIES:

- (A) Douthitt Heavy Duty Model 26 Silent Air Pump instead of standard pump and motor (this pump requires compressed air) see page 17 for details.
- (B) 5-Drawer Ball Bearing Cabinet mounted inside frame 30 x 35 through 40 x 45 (Drawer I.D. 32 x 43) 48 x 55 (Drawer I.D. 38 x 50) Larger cabinets available.
- (C) Opaque Curtain Assembly - Eliminate Light Spillage, Fully Fire Retardant and OSHA approved material

Manufactured by: The Douthitt Corporation, 245 Adair St., Detroit, Michigan 48207
Toll Free 1-800-DOUTHIT(T) Phone 313-259-1565
Established 1919 · Fax No. 313-259-6806
www.douthittcorp.com · E-Mail: em@douthittcorp.com